



Divina 3

Abrasion

Approx. 45.000 Martindale rubs, EN ISO 12947

Abrasion test results exceeding ACT performance guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention

Pilling

Note 3 EN ISO 12945

Seam slippage

Seam parallel to warp: 2.0mm parallel to weft: 2.0 mm
EN ISO 13 936-2 180 Newton

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12
Wet note 3-5 ISO 105-X12

Absorption

0.60/Class C (flat), 0.70/Class C (weaved) EN ISO 354

Airflow

678 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3
ASTM E84 Class A Adhered
ASTM E84 Class B Unadhered
ASTM E84 Class A Unadhered with treatment *
BS 5852 Crib 5
BS 5852 part 1
BS 5867 part 2 type B
CAN ULC S109 with treatment *
EN 1021-1/2
EN 13501, C-s1, d0, glued
GB 50222 B1 with treatment (Chinese) *
IMO FTP Code 2010 Part 8
NF D 60 013
NFPA 260
NFPA 701 with treatment *
ÖNORM B1/Q1
SN 198 898 5.3 with treatment *
UNI 9175 1IM
US Cal. Bull. 117-2013

Free from added flame retardant chemicals as standard

** To pass this test flame retardant treatment is necessary. We are looking into more environmentally friendly alternatives but for now, the external finisher may use a treatment containing halogen-based flame retardants*

Divina 3

Design: Finn Sködt

Type: Upholstery

Composition: 100% new wool

Yarn type: Woolen

Binding: Broken twill

Width: Approx. 150 cm, 59 inches

Weight: Approx. 840 g/lin.m, 27.1 oz/ly

Repeat: None

Foreign fibers may occur in light colours

Colour difference may occur

Cleaning: Vacuum clean frequently, ideally every week. Remove stains as soon as they occur, with clean warm water or sparkling water. Please be aware that stain removal will cause a darker area as the wool fibers rise when exposed to water. This can only be reduced by gentle atomizing water over the entire furniture. Extraction clean when necessary. Avoid using steam.

More info: Care and maintenance kvadrat.dk



10 year warranty



ACT Guidelines Woven fabrics

Flammability

US Cal. Bull. 117-2013

Dry & Wet Crocking

Dry Crocking: Grade 4.5

Wet Crocking: Grade 3.0

Colour Fastness to Light

Grade 4.0 minimum 40 hours

Physical properties

Pilling Class 3

Breaking Strength warp 100 / weft 82 lbs.

Seam Slippage warp 98.5 / weft 79 lbs.

Abrasion

45.000 cycles Martindale – High Traffic / Public Spaces

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/
give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Complies with Möbelfakta

Very good abrasion

Very good lightfastness

Flame retardant

Green building certificates

Greenguard Gold: Low chemical emission

Environmental Product Declaration (EPD): Based on a LCA following EN 15804 and follow the standard of ISO 14040

Health Product Declaration (HPD): Declaring textile content and substance

Country of origin

United Kingdom

Launch

1984

Warranty

10 years. See terms and conditions on kvadrat.dk

Kvadrat packaging and cardboard is recyclable. Cardboard material is FSC certified and / or contains recycled content.

For further information

kvadrat.dk

Environmental benefits

EU Ecolabel compliant

No content of PFCs or 'PFAS'

REACH compliant

Californian Proposition 65 list compliant

BC Red list compliant

California Proposition 65 compliant

Kvadrat