



Hallingdal 65

Abrasion

Approximately 100.000 Martindale rubs, EN ISO 12947

Pilling

Note 3-4, EN ISO 12945

Seam slippage

Warp: 4.5 mm Weft: 4 mm

Lightfastness

Note 5-7, ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

Absorption

0.45/Class D (flat), 0.70/Class C (waved)

Airflow

210 Pa s/m

Flame resistance

AS/NZS 1530.3

AS/NZS 3837

BS 5852 Crib 5

BS5852 part 1

DIN 4102 B2

EN 1021-1/2

IMO FTP Code 2010: Part 8

NF D 60 013

NFPA 260

Önorm B1/Q1

SN 198 898 5.3 with treatment

UNI 9175 1IM

US Cal. Bull. 117 – 2013

No use of brominated flame retardants

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb / give off humidity Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Very good abrasion

Good lightfastness

Flame retardant

Environmental benefits

Complies with EU Ecolabel

We adhere to the limits set by the Danish Environmental Protection Agency's "List of Undesirable Substances"

Complies with REACH

Reduced emissions

Greenguard and Greenguard Gold certified

www.greenguard.com

Hallingdal 65

Design: Nanna Ditzel

Type: Upholstery

Composition: 70% new wool, 30% viscose

Yarn type: Stapel

Binding: Plain

Width: 130 cm

Weight: Approximately 795 g/lin.m Repeat: None

Cleaning: Vacuuming and dry cleaning

More info: Maintenance instruction – please see website



10 year warranty   



kvadrat

For further information

kvadrat.dk