



Raas

Abrasion

Approximately 100.000 Martindale rubs, EN ISO 12947

Pilling

Note 4-5 EN ISO 12945

Seam slippage

Warp: 5.7 mm, Weft: 2.2 mm

Lightfastness

Note 6-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 4-5 ISO 105-X12

Flame resistance

BS 5852 Crib 5 with treatment

BS 5852 ignition source 3

BS 5852 part 1

EN 1021-1/2

IMO FTP Code 2010:Part 8

NF D 60 013

UNI 9175 1IM

US Cal. Bull. 117-2013

Önorm B2/Q1

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Very good abrasion

Very good lightfastness

Permanent flame retardant

Environmental benefits

No use of AZO dyes, which may split off carcinogenic acryl amines

No use of dyes containing heavy metals/ complies with ETAD norm

No use of brominated flame retardants

We adhere to the limits set by the Danish Environmental Protection Agency's 'List of undesirable substances'

Complies with REACH

Reduced emission

Greenguard and Greenguard Gold certified

www.greenguard.org

For further information

kvadrat.dk

Raas

Design: Doshi Levien

Type: Upholstery

Composition: 92% new wool, 8% nylon

Yarn type: Worsted

Binding: Hopsack variant

Width: 140 cm (app. 55 inches)

Weight: app. 770 g/lin.m

Repeat: None

Cleaning: Vacuuming and dry cleaning

More info: Maintenance instruction—please see website

