



## Steelcut Trio 2

### Abrasion

Approximately 80.000 Martindale rubs, EN ISO 12947

### Pilling

Note 3-4, EN ISO 12945

### Lightfastness

Note 5-7, ISO 105-B02

### Flame resistance

EN 1021-1/2

BS 5852, ignition source 2-3

DIN 4102 B2

Önorm B1/Q1

Italian Class 1IM

US Cal. Tech. Bull. 117, Sec. E

IMO A.652(16)

Crib 5 and M2 when flame protected

No use of brominated flame retardants

### Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its

ability to absorb / give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

### Quality benefits

Very good abrasion

Good lightfastness

Flame retardant

### Environmental benefits

No use of AZO dyes, which may split off carcinogenic acrylamines

No use of dyes containing heavy metals

No content of formaldehyde

No use of chlorine

No use of brominated flame retardants

Biodegradable spinning oil

We adhere to the limits set by the the Danish Environmental Protection Agency's "List of undesirable substances"

### Reduced Emissions

Indoor air quality certified under the Greenguard for Children & Schools Program, complies with CA Section 01350 requirements for schools and accepted for CHPS Low-Emitting Materials credits. [www.greenguard.org](http://www.greenguard.org)

For further information

[www.kvadrat.dk](http://www.kvadrat.dk)

### Steelcut Trio 2

Design: Frans Dijkmeijer and Giulio Ridolfo

Type: Upholstery

Composition: 90% new wool, 10% nylon

Yarn type: Stapel, worsted

Binding: Semi-plain

Width: 140 cm

Weight: Approximately 880 g/lin.m

Repeat: None

Cleaning: Dry clean or clean with foam detergents.

Stain removal: See special guide

