



# San

## Abrasion

Approximately 60.000 Martindale rubs, EN ISO 12947

## Pilling

Note 3-4 EN ISO 12945

## Seam slippage

Warp: 5.5 mm, Weft: 9.5 mm

## Lightfastness

Note 5-7 ISO 105-B02

## Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

## Flame resistance

BS 5852 Part 1

BS 5852 Crib 5 with treatment

EN 1021-1/2

IMO FTP Code 2010:Part 8

NF D 60 013

UNI 9175 1IM

US Cal. Bull. 117-2013

## Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb/give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

## Quality benefits

Very good abrasion

Very good lightfastness

Permanent flame retardant

## Environmental benefits

No use of AZO dyes, which may split off carcinogenic acryl amines

No use of dyes containing heavy metals/ complies with ETAD norm

No use of brominated flame retardants

We adhere to the limits set by the Danish Environmental Protection Agency's 'List of undesirable substances'

Complies with REACH

## Reduced emission

Greenguard and Greenguard Gold certified  
[www.greenguard.org](http://www.greenguard.org)

For further information  
[kvadrat.dk](http://kvadrat.dk)

## San

Design: Louise Sigvardt

Type: Upholstery

Composition: 92% new wool, 8% nylon

Yarn type: Worsted

Binding: Jacquard

Width: 140 cm (app. 55 inches)

Weight: app. 370 g/lin.m

Repeat: None

Cleaning: Vacuuming and dry cleaning

More info: Maintenance instruction—please see website

